

# INSTALLATION MANUAL

## INSTALLATION GUIDE

- After receiving the package, please confirm whether the packaging is in good condition.
- Due to long-distance transportation or packing compression, the floor liners may be slightly wrinkled. The following ways can help you recover them smoothly:
  - ▲ Lay it flat on the ground and wait for automatic recovery. Some severely deformed areas can be twisted by hand to help recovery.
  - ▲ When the temperature is low, recovery will be more difficult, you can use equipment such as electric hair dryer to help recovery, or use hot water to help recovery.
- Remove the factory floor liner and keep the floor clean before installing the new floor liner.
- Move the two front seats to the last position so that the floor liner is in line with the car floor shape and lock the clips to the floor with the holes in the floor liner in the corresponding position.
- Last step, check whether the floor liners interfere with the accelerator, brake, etc.
- Our Floor mats & cargo liner need to be heated at 428°F during the production process, there may be some smell when you receive the product .please don't worry about it, Please put it outdoors (the ambient temperature is greater than 68°F and it will disappear faster) or lay it flat in other places, they will disappear within a week.

## Notice:

If you found it not fits perfectly, please reconfirm the order matches your car

- ★ **Whether choice correct year for floor liners;**
- ★ **Whether it has different configuration;**
- ★ **Whether there is a distinction between gasoline and hybrid cars;**

### custom fit



DRIVER SIDE

SECOND ROW

PASSENGER SIDE



### easy clean



The photo only for reference